

# TYPE APPROVAL CERTIFICATE

**This is to certify:****That the Low Voltage Cable**

with type designation(s)

**U-HFFRAT m WSR, U-HFFRAT m(I) WSR**

Issued to

**Unika Universal Kablo San. ve Tic. A.S.  
ISTANBUL, Turkey**

is found to comply with

**DNV GL rules for classification – Ships, offshore units, and high speed and light craft****Application :****Products approved by this certificate are accepted for installation on all vessels classed by DNV GL.**

Type	Rated voltage (V)	Temp. class (°C)
U-HFFRAT m WSR	250	90
U-HFFRAT m(I) WSR	250	90

Issued at **Høvik** on **2018-02-09**for **DNV GL**This Certificate is valid until **2023-02-08**.DNV GL local station: **Istanbul**Approval Engineer: **Georgy Abramenko**

---

**Andreas Kristoffersen  
Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



## Product description

Construction:  
 Conductors: Annealed bare or tinned stranded copper according to IEC 60228 class2 or class 5  
 Tape: Helical applied fire resistant tape  
 Core insulation: Cross-linked polyolefin halogen-free, HF90  
 Tape (m(I) variants): Polyester tape  
 Wire (m(I) variants): Tinned copper drain wire  
 Tape (m(I) variants): Metal coated polyester tape  
 Bedding: Polyester tape or halogen free extruded compound (optional)  
 Tape: Fire resistant glass fiber tape + double copper backed polyester tape + fire resistant glass fiber tape + polyester tape (optional)  
 Armour: Tinned or bare copper wire braid  
 Outer jacket: Halogen free extruded compound SHF1 or SHF2.

Number of cores														Number of elements		Cross section	
1	2	3	4	5	6	7	8	9	10	12	14	16	18	2	3	0,75	1,5
19 24																	
27 33 37														2	3	0,75	1,5

## Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

This cable is fire resistant according to IEC 60331.

## Type Approval documentation

Data sheets: [4253718 rev.1 dated 16.02.2017.](#)  
[4253717 rev.1 dated 16.02.2017.](#)  
[Data table doc. No. 4253717-1 dated 24.01.2018.](#)  
[Data table doc. No. 4253718-2 dated 23.12.2017.](#)  
 Test report no: [test report dated 18.01.2018](#)  
[test report 386218 dated 01.2018](#)

## Tests carried out

Standard	Release	General description	Limitation
IEC 60092-350	2014-08	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-360	2014-04	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	
IEC 60092-376	2017-05	Cables for control and instrumentation circuits 150/250 V (300 V)	
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables - Part 1: Determination of the halogen acid gas content	Low Halogen: <0,5% Halogen
IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS/mm

Job Id: **262.1-027593-1**  
Certificate No: **TAE00002KR**

IEC 61034-1/2	2005-04	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke Light transmittance $\geq 60\%$
IEC 60331-1/2	2009-05	Fire resistance / Circuit integrity – Test for method for fire <i>with shock</i> at temperature of at least 830°C for cables rated up to and including 0,6/1 kV	Minimum 90 min
IEC 60332-3-22	2009-02	Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A	Charred portion of sample does not exceed 2,5m above bottom edge of burner.
BS 8491	2008-01	Method for assessment of fire integrity of large diameter power cables for use as components for smoke and heat control systems and certain other active fire safety systems	
EN50200	2015-12	Method of test for resistance to fire of unprotected small cables for use in emergency circuits. The standard also includes in Annex E a means of applying water spray to the cable during the test.	
CSA C22.2 No. 03	2009	4.12 Flexibility at any specified temperature 4.13 Abnormal low temperature – impact	Cold bend: -40°C Cold impact: -35°C

### Marking of product

UNIKA – U-HFFRAT m WSR - size – 250 V or UNIKA – U-HFFRAT m(I) WSR - size – 250 V – IEC 60331 - IEC 60332-3-22 – Lot No.

### Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine tests (RT) and selected type tests (ref. to applicable class programs) checked (if not available these tests shall be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE