

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Electric Power Cable**with type designation(s)
MGCH, MGCH EMC, MGCH VFD

Issued to

Unika Universal Kablo San. ve Tic. A.S.
ISTANBUL, Turkey

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft**Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.**

Type	Rated voltage (kV)	Temp. class (°C)
MGCH	0,6/1	90
MGCH EMC	0,6/1	90
MGCH VFD	1,8/3	90

Issued at **Hamburg** on **2018-12-18**for **DNV GL**This Certificate is valid until **2023-12-17**.DNV GL local station: **Istanbul**Approval Engineer: **Carsten Hunsalz**.....
Arne Schaarmann
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: 262.1-029941-1
 Certificate No: TAE000000N
 Revision No: 1

Product description

Construction:
 Conductors: Plain or tinned stranded copper class 2 or class 5
 Core insulation: HEPR
 Inner covering: Halogen free compound
 Screen: Metal coated polyester tape (EMC, VFD types)
 Metal covering: Plain or tinned copper wire braid
 Outer sheath: SHF1

Number of cores x conductor cross-section mm ²
MGCH
1 x 25
1 x 95
2 x 1,5
2 x 2,5
2 x 4
2 x 6
3 x 1,5
3 x 2,5
3 x 4
3 x 6
3 x 10
3 x 16

Number of cores x conductor cross-section mm ²
3 x 25
3 x 35
3 x 50
3 x 70
3 x 95
4 x 1,5
5 x 1,5
7 x 1,5
10 x 1,5
14 x 1,5
16 x 1,5
19 x 1,5

Number of cores x conductor cross-section mm ²
MGCH EMC
3 x 2,5
3 x 6
3 x 16
3 x 35
3 x 70
3 x 95
MGCH VFD
3 x 10
3 x 16
3 x 35
3 x 50
3 x 95

Application/Limitation

General power and lighting. Control.

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Type Approval documentation

Data sheets.
 Test reports.

Tests carried out

Standard	Release	General description	Limitation
IEC 60092-350	2014-08	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-360	2014-04	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	
IEC 60092-353	2016-09	Electrical installations in ships - Part 353: Power cables for rated voltages 1 kV and 3 kV	

Job Id: 262.1-029941-1
Certificate No: TAE000000N
Revision No: 1

IEC 60332-3-22	2018-07	Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A	Charred portion of sample does not exceed 2,5m above bottom edge of burner.
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables - Part 1: Determination of the halogen acid gas content	Low Halogen: <0,5% Halogen
IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS/mm
IEC 61034-1/2	2013-06	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke Light transmittance ≥60%

Marking of product

UNIKA KABLO - MGCH or MGCH EMC or MGCH VFD – size - 0,6/1 kV or 1,8/3 kV - IEC 60332-3-22 - Lot No.

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE