

H01N2-D H01N2-E

100/100 V Kaynak Kabloları
100/100 V Welding Cables



YAPI

- 1 İletken**
H01N2-D: Çok ince telli bakır tel HD 383
H01N2-E: Süper ince telli bakır tel

- 2 Ayırıcı**
Polyster veya kağıt bant

- 3 Dış Kılıf**
Kauçuk

**Standart TS 9767 ve
HD 22.6 S2**

CONSTRUCTION

Conductor
H01N2-D: Very fine stranded copper wire HD 383
H01N2-E: Super fine stranded copper wire HD 383

Separator
Polyester or paper tape

Outer Sheath
Rubber

**Standard TS 9767 and
HD 22.6 S2**

H01N2-D

100/100 V Kaynak Kabloları / 100/100 V Welding Cables

Kesit (mm ²) Cross-Section	1	1,5	2,5	4	6	10	16	25	35	50	70	95	120	150	185	240	300
Max. DC Direnç (Ω/km) Max. DC Resistance	18,1	12,1	7,4	4,61	3,08	1,83	1,15	0,727	0,524	0,387	0,268	0,193	0,154	0,126	0,100	0,0762	0,0601
Nominal Ağırlık (kg/km) / Nominal Çap (mm) / Nominal Weight (kg/km) / Nominal Diameter (mm)																	
Damar Sayısı Number of Cores	1					150/9	210/10	300/11	390/13	550/14	750/17	1000/19	1260/22	1560/24	1790/26		

H01N2-E

Damar Sayısı Number of Cores	1					120/7	180/8	260/10	350/11	510/14	700/16	950/18	1160/20				
---------------------------------	---	--	--	--	--	-------	-------	--------	--------	--------	--------	--------	---------	--	--	--	--

Diğer damar sayılı kablolar ve kesitler istek üzerine üretilebilir. / Other number of cores and cross sections can be manufactured upon request.