



Confirmation of Product Type Approval

Company Name: UNIKA UNIVERSAL KABLO SAN. VE TIC A.S.

Address: VELIKOY ORGANIZE SANAYI BOLGESI SANAYI MAH. 3.CADDE NO.4 CERKEZKOY
TEKIRDAG 59550 Turkey

Product: Cable, Electric

Model(s): POWER CABLES - Models: U-HF m, U-HFA m, U-HFA m EMC (U-HFA m VFD), U-HFA m (C), U-HFFR m, U-HFFRA m, U-HFFRA m (C) COMMUNICATION CABLES - Models: U-HFT m, U-HFT m (I), U-HFT m (C), U-HFT m (I+C), U-HFAT m, U-HFAT m (I), U-HFAT m (C), U-HFAT m (I+C), U-HFFRT m, U-HFFRT m (I), U-HFFRT m (C), U-HFFRT m (I+C), U-HFFRAT m, U-HFFRAT m (I), U-HFFRAT m (C), U-HFFRAT m (I+C)

Endorsements:

| Certificate Type | Certificate Number | Issue Date | Expiry Date |
|---------------------------------|--------------------|-------------|-------------|
| Product Design Assessment (PDA) | 26-0507545-PDA | 05-JUN-2026 | 04-JUN-2031 |
| Manufacturing Assessment (MA) | 23-6060224 | 06-OCT-2023 | 05-OCT-2028 |
| Product Quality Assurance (PQA) | NA | NA | NA |

Tier

3 - Type Approved, unit certification not required

Intended Service

Power and Communication Cables for Marine and Offshore Applications.

Description

U-HF m 0. 6/1 kV unarmored power cables;

U-HFA m 0. 6/1 kV armored power cables;

U-HFA m EMC (U-HFA m VFD) 0. 6/ 1kV armored power cables;

U-HFA m (C) 0, 6/1 kV armored power cables;

U-HFFR m 0. 6/1 kV fire resistant unarmored power cables;

U-HFFRA m 0. 6/1 kV fire resistant armored power cables;

U-HFFRA m (C) 0, 6/1 kV fire resistant armored power cables;

U-HFT m 250 V unarmored communication cables;

U-HFT m (I) 250 V unarmored communication cables;

U-HFT m (C) 250 V unarmored communication cables;
U-HFT m (I+C) 250 V unarmored communication cables;
U-HFAT m 250 V armored communication cables;
U-HFAT m (I) 250 V armored communication cables;
U-HFAT m (C) 250 V armored communication cables;
U-HFAT m (I+C) 250 V armored communication cables;
U-HFFRT m 250 V fire resistant unarmored communication cables;
U-HFFRT m (I) 250 V fire resistant unarmored communication cables;
U-HFFRT m (C) 250 V fire resistant unarmored communication cables;
U-HFFRT m (I+C) 250 V fire resistant unarmored communication cables;
U-HFFRAT m 250 V fire resistant armored communication cables;
U-HFFRAT m (I) 250 V fire resistant armored communication cables;
U-HFFRAT m (C) 250 V fire resistant armored communication cables; and
U-HFFRAT m (I+C) 250 V fire resistant armored communication cables.

Please refer to the Attachment for the approved sizes of each cable model.

Ratings

Rated Voltage: 0.6/1 kV (power cables), 250 V (communication cables)

Maximum rated conductor temperature: 90 deg C;

Maximum current carrying capacity for power cables as per 4-8-3/Table 6 of the ABS Rules for Building and Classing Marine Vessels.

Service Restrictions

1. Unit Certification is not required for this product. If the manufacturer or purchaser request an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances, must be clearly defined.
2. This product is not to be used for electric propulsion systems.
3. Galvanized steel wire braid armor is not to be applied to single core alternating current cables.

Comments

1. The Manufacturer has provided a declaration about the control of, or the lack of Asbestos in this product.
2. UNIKA is the test lab location for all the manufacturer's test reports listed in the "Notes, Drawings and Documentation" section.

Notes, Drawings and Documentation

Drawing No. 001, Quality Declaration-31, Revision: 01, Pages: 01

Drawing No. 003, GAP Analysis, Revision: 01, Pages: 04

Previously Submitted Drawings:

1. UNIKA Test report for the cable model U-HF m dated 23 March 2021.
2. UNIKA Test report for the cable model U-HFA m dated 23 March 2021.
3. UNIKA Test report for the cable model U-HFA m EMC dated 23 March 2021.
4. UNIKA Test report for the cable model U-HFFR m dated 23 March 2021.
5. UNIKA Test report for the cable model U-HFFRA m dated 23 March 2021.
6. UNIKA Test report for the cable model U-HFT m dated 23 March 2021.
7. UNIKA Test report for the cable model U-HFT m (I) dated 23 March 2021.
8. UNIKA Test report for the cable model U-HFT m (C) dated 23 March 2021.
9. UNIKA Test report for the cable model U-HFT m (I+C) dated 23 March 2021.
10. UNIKA Test report for the cable model U-HFAT m dated 23 March 2021.
11. UNIKA Test report for the cable model U-HFAT m (I) dated 23 March 2021.
12. UNIKA Test report for the cable model U-HFAT m (C) dated 23 March 2021.
13. UNIKA Test report for the cable model U-HFAT m (I+C) dated 23 March 2021.
14. UNIKA Test report for the cable model U-HFFRT m dated 23 March 2021.
15. UNIKA Test report for the cable model U-HFFRT m (I) dated 23 March 2021.
16. UNIKA Test report for the cable model U-HFFRT m (C) dated 23 March 2021.
17. UNIKA Test report for the cable model U-HFFRT m (I+C) dated 23 March 2021.
18. UNIKA Test report for the cable model U-HFFRAT m dated 23 March 2021.
19. UNIKA Test report for the cable model U-HFFRAT m (I) dated 23 March 2021.
20. UNIKA Test report for the cable model U-HFFRAT m (C) dated 23 March 2021.
21. UNIKA Test report for the cable model U-HFFRAT m (I+C) dated 23 March 2021.
22. UNIKA Test report for the cable model U-HFA m (C) dated 2 April 2021.
23. UNIKA Test report for the cable model U-HFA m (C) dated 17 May 2021.
24. UNIKA Test report for the cable model U-HFFRA m (C) dated 2 April 2021.
25. UNIKA Test report for the cable model U-HFFRA m (C) dated 17 May 2021.
26. UNIKA Durability of Print test report for all cable models dated 17 May 2021.
27. Description of cable models and sizes.

Term of Validity

This Product Design Assessment (PDA) Certificate remains valid until 04/Jun/2031 or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

ABS Rules

Rules for Conditions of Classification Part 1A (2026): 1A-1-4/7.7, 1A-1-A3, 1A-1-A4, which covers the following:

Rules for Building and Classing Marine Vessels (2026): 4-8-3/9.1, 4-8-3/9.3, 4-8-3/9.4, 4-8-3/9.5, 4-8-3/9.7, 4-8-3/9.9, 4-8-3/9.17

Rules for Conditions of Classification Part 1B (2025): 1B-1-4/9.7, 1B-1-A2, 1B-1-A3, which cover the following:

Rules for Building and Classing Offshore Units (2026): 4-3-4/7.1.1, 4-3-4/7.1.2, 4-3-4/7.1.3, 4-3-4/7.1.4

International Standards

IEC 60092-353:2024

IEC 60092-376:2025 and the applicable IEC Standards referred to therein (IEC 60092-350:2020, IEC 60092-360:2021, IEC 60331-1:2018, IEC 60331-2:2018, IEC 60332-3-22:2018)

EU-MED Standards

NA

National Standards

CSA C22.2 No. 0.3-09 National Standard of Canada (reaffirmed 2023) [refers to Section 5.12 Abnormal low temperature, cold impact tests as per CSA C22.2 No. 2556:2021].

Government Standards

NA

Other Standards

NA



A handwritten signature in blue ink, appearing to read 'Joseph W. ...', is written over the printed name.

Corporate ABS Programs
American Bureau of Shipping
Print Date and Time: 05-Jun-2026 5:23

ABS has used due diligence in the preparation of this certificate, and it represents the information on the product in the ABS Records as of the date and time the certificate is printed.

If the Rules and/or standards used in the PDA evaluation are revised or if there is a design modification (whichever occurs first), a PDA revalidation may be necessary.

The continued validity of the MA is dependent on completion of satisfactory audits as required by the ABS Rules. The validity of both PDA and MA entitles the product to receive a **Confirmation of Product Type Approval**.

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or

prior to the effective date of the ABS Rules and standards applied at the time of PDA issuance. ABS makes no representations regarding Type Approval of the Product for use on vessels, MODUs or facilities built after the date of the ABS Rules used for this evaluation.

Type Approval requires Drawing Assessment, Prototype Testing and assessment of the manufacturer's quality assurance and quality control arrangements. The manufacturer is responsible to maintain compliance with all specifications applicable to the product design assessment. Unless specifically indicated in the description of the product, certification under type approval does not waive requirements for witnessed inspection or additional survey for product use on a vessel, MODU or facility intended to be ABS classed or that is presently in class with ABS.

Due to wide variety of specifications used in the products ABS has evaluated for Type Approval, it is part of our contract that; whether the standard is an ABS Rule or a non-ABS Rule, the Client has full responsibility for continued compliance with the standard.

Questions regarding the validity of ABS Rules or the need for supplemental testing or inspection of such products should, in all cases, be addressed to ABS.

Manufacturer: UNIKA UNIVERSAL KABLO SAN. VE T.

Models: Listed below

Issue date: 03/06/2026

Expiration date: TBC

PDA Number: 26-0507545-PDA



PDA Cable Models & Ranges

POWER CABLES - Models:

- U-HF m
- U-HFA m
- U-HFA m EMC (U-HFA m VFD)
- U-HFA m (C)
- U-HFFR m
- U-HFFRA m
- U-HFFRA m (C)

U-HF m (0,6/1 kV unarmored power cables with tinned or bare copper conductors class 2 or 5, XLPE insulation, halogen-free inner covering, outer jacket SHF 1 or SHF 2)

- 1x1, 1x1.5, 1x2.5, 1x4, 1x6, 1x10, 1x16, 1x25, 1x35, 1x50, 1x70, 1x95, 1x120, 1x150, 1x185, 1x240, 1x300 mm².
- 2x1, 2x1.5, 2x2.5, 2x4, 2x6, 2x10, 2x16, 2x25, 2x35, 2x50, 2x70, 2x95 mm².
- 3x1, 3x1.5, 3x2.5, 3x4, 3x6, 3x10, 3x16, 3x25, 3x35, 3x50, 3x70, 3x95, 3x120, 3x150, 3x185, 3x240 mm².
- 4x1, 4x1.5, 4x2.5, 4x4, 4x6, 4x10, 4x16, 4x25, 4x35, 4x50, 4x70, 4x95, 4x120, 4x150 mm².
- 5x1, 5x1.5, 5x2.5, 5x4, 5x6, 5x10, 5x16, 5x25, 5x35, 5x50, 5x70, 5x95 mm².
- 7x1, 7x1.5, 7x2.5 mm².
- 8x1, 8x1.5, 8x2.5 mm².
- 10x1, 10x1.5, 10x2.5 mm².
- 12x1, 12x1.5, 12x2.5 mm².
- 16x1, 16x1.5, 16x2.5 mm².
- 18x1, 18x1.5, 18x2.5 mm².
- 19x1, 19x1.5, 19x2.5 mm².
- 24x1, 24x1.5, 24x2.5 mm².
- 27x1, 27x1.5, 27x2.5 mm².
- 30x1, 30x1.5, 30x2.5 mm².
- 37x1, 37x1.5, 37x2.5 mm².

U-HFA m (0,6/1 kV armored power cables with tinned or bare copper conductors class 2 or 5, XLPE insulation, halogen-free inner covering, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 1x1, 1x1.5, 1x2.5, 1x4, 1x6, 1x10, 1x16, 1x25, 1x35, 1x50, 1x70, 1x95, 1x120, 1x150, 1x185, 1x240, 1x300 mm².
- 2x1, 2x1.5, 2x2.5, 2x4, 2x6, 2x10, 2x16, 2x25, 2x35, 2x50, 2x70, 2x95 mm².
- 3x1, 3x1.5, 3x2.5, 3x4, 3x6, 3x10, 3x16, 3x25, 3x35, 3x50, 3x70, 3x95, 3x120, 3x150, 3x185, 3x240 mm².
- 4x1, 4x1.5, 4x2.5, 4x4, 4x6, 4x10, 4x16, 4x25, 4x35, 4x50, 4x70, 4x95, 4x120, 4x150 mm².
- 5x1, 5x1.5, 5x2.5, 5x4, 5x6, 5x10, 5x16, 5x25, 5x35, 5x50, 5x70, 5x95 mm².
- 7x1, 7x1.5, 7x2.5 mm².
- 8x1, 8x1.5, 8x2.5 mm².
- 10x1, 10x1.5, 10x2.5 mm².
- 12x1, 12x1.5, 12x2.5 mm².
- 16x1, 16x1.5, 16x2.5 mm².
- 18x1, 18x1.5, 18x2.5 mm².
- 19x1, 19x1.5, 19x2.5 mm².
- 24x1, 24x1.5, 24x2.5 mm².
- 27x1, 27x1.5, 27x2.5 mm².
- 30x1, 30x1.5, 30x2.5 mm².
- 37x1, 37x1.5, 37x2.5 mm².

U-HFA m EMC (0,6/1 kV armored power cables with tinned or bare copper conductors class 2 or 5, XLPE insulation, halogen-free inner covering, copper/polyester tape, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 1x1, 1x1.5, 1x2.5, 1x4, 1x6, 1x10, 1x16, 1x25, 1x35, 1x50, 1x70, 1x95, 1x120, 1x150, 1x185, 1x240, 1x300 mm².
- 2x1, 2x1.5, 2x2.5, 2x4, 2x6, 2x10, 2x16, 2x25, 2x35, 2x50, 2x70, 2x95 mm².
- 3x1, 3x1.5, 3x2.5, 3x4, 3x6, 3x10, 3x16, 3x25, 3x35, 3x50, 3x70, 3x95, 3x120, 3x150, 3x185, 3x240 mm².
- 3x16+3x2.5, 3x25+3x4, 3x25+3x6, 3x35+3x6, 3x50+3x10, 3x70+3x10, 3x70+3x16, 3x95+3x16, 3x120+3x25, 3x150+3x25, 3x185+3x25, 3x185+3x35, 3x240+3x35, 3x240+3x50 mm².
- 4x1, 4x1.5, 4x2.5, 4x4, 4x6, 4x10, 4x16, 4x25, 4x35, 4x50, 4x70, 4x95, 4x120, 4x150 mm².
- 5x1, 5x1.5, 5x2.5, 5x4, 5x6, 5x10, 5x16, 5x25, 5x35, 5x50, 5x70, 5x95 mm².

U-HFA m (C) (0,6/1 kV armored power cables with tinned or bare copper conductors class 2 or 5, XLPE insulation, copper drain wire, metal coated polyester tape, halogen-free inner covering, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 1x1, 1x1.5, 1x2.5, 1x4, 1x6, 1x10, 1x16, 1x25, 1x35, 1x50, 1x70, 1x95, 1x120, 1x150, 1x185, 1x240, 1x300 mm².
- 2x1, 2x1.5, 2x2.5, 2x4, 2x6, 2x10, 2x16, 2x25, 2x35, 2x50, 2x70, 2x95 mm².
- 3x1, 3x1.5, 3x2.5, 3x4, 3x6, 3x10, 3x16, 3x25, 3x35, 3x50, 3x70, 3x95, 3x120, 3x150, 3x185, 3x240 mm².
- 4x1, 4x1.5, 4x2.5, 4x4, 4x6, 4x10, 4x16, 4x25, 4x35, 4x50, 4x70, 4x95, 4x120, 4x150 mm².
- 5x1, 5x1.5, 5x2.5, 5x4, 5x6, 5x10, 5x16, 5x25, 5x35, 5x50, 5x70, 5x95 mm².
- 7x1, 7x1.5, 7x2.5 mm².
- 8x1, 8x1.5, 8x2.5 mm².
- 10x1, 10x1.5, 10x2.5 mm².
- 12x1, 12x1.5, 12x2.5 mm².
- 16x1, 16x1.5, 16x2.5 mm².
- 18x1, 18x1.5, 18x2.5 mm².
- 19x1, 19x1.5, 19x2.5 mm².
- 24x1, 24x1.5, 24x2.5 mm².
- 27x1, 27x1.5, 27x2.5 mm².
- 30x1, 30x1.5, 30x2.5 mm².
- 37x1, 37x1.5, 37x2.5 mm².

U-HFFR m (0,6/1 kV fire resistant unarmored power cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, halogen-free inner covering, outer jacket SHF 1 or SHF 2)

- 1x1, 1x1.5, 1x2.5, 1x4, 1x6, 1x10, 1x16, 1x25, 1x35, 1x50, 1x70, 1x95, 1x120, 1x150, 1x185, 1x240, 1x300 mm².
- 2x1, 2x1.5, 2x2.5, 2x4, 2x6, 2x10, 2x16, 2x25, 2x35, 2x50, 2x70, 2x95 mm².
- 3x1, 3x1.5, 3x2.5, 3x4, 3x6, 3x10, 3x16, 3x25, 3x35, 3x50, 3x70, 3x95, 3x120, 3x150, 3x185, 3x240 mm².
- 4x1, 4x1.5, 4x2.5, 4x4, 4x6, 4x10, 4x16, 4x25, 4x35, 4x50, 4x70, 4x95, 4x120, 4x150 mm².
- 5x1, 5x1.5, 5x2.5, 5x4, 5x6, 5x10, 5x16, 5x25, 5x35, 5x50, 5x70, 5x95 mm².
- 7x1, 7x1.5, 7x2.5 mm².
- 8x1, 8x1.5, 8x2.5 mm².
- 10x1, 10x1.5, 10x2.5 mm².
- 12x1, 12x1.5, 12x2.5 mm².
- 16x1, 16x1.5, 16x2.5 mm².
- 18x1, 18x1.5, 18x2.5 mm².
- 19x1, 19x1.5, 19x2.5 mm².
- 24x1, 24x1.5, 24x2.5 mm².

U-HFFR m (0,6/1 kV fire resistant unarmored power cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, halogen-free inner covering, outer jacket SHF 1 or SHF 2)

- 27x1, 27x1.5, 27x2.5 mm².
- 30x1, 30x1.5, 30x2.5 mm².
- 37x1, 37x1.5, 37x2.5 mm².

U-HFFRA m (0,6/1 kV fire resistant armored power cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, halogen-free inner covering, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 1x1, 1x1.5, 1x2.5, 1x4, 1x6, 1x10, 1x16, 1x25, 1x35, 1x50, 1x70, 1x95, 1x120, 1x150, 1x185, 1x240, 1x300 mm².
- 2x1, 2x1.5, 2x2.5, 2x4, 2x6, 2x10, 2x16, 2x25, 2x35, 2x50, 2x70, 2x95 mm².
- 3x1, 3x1.5, 3x2.5, 3x4, 3x6, 3x10, 3x16, 3x25, 3x35, 3x50, 3x70, 3x95, 3x120, 3x150, 3x185, 3x240 mm².
- 4x1, 4x1.5, 4x2.5, 4x4, 4x6, 4x10, 4x16, 4x25, 4x35, 4x50, 4x70, 4x95, 4x120, 4x150 mm².
- 5x1, 5x1.5, 5x2.5, 5x4, 5x6, 5x10, 5x16, 5x25, 5x35, 5x50, 5x70, 5x95 mm².
- 7x1, 7x1.5, 7x2.5 mm².
- 8x1, 8x1.5, 8x2.5 mm².
- 10x1, 10x1.5, 10x2.5 mm².
- 12x1, 12x1.5, 12x2.5 mm².
- 16x1, 16x1.5, 16x2.5 mm².
- 18x1, 18x1.5, 18x2.5 mm².
- 19x1, 19x1.5, 19x2.5 mm².
- 24x1, 24x1.5, 24x2.5 mm².
- 27x1, 27x1.5, 27x2.5 mm².
- 30x1, 30x1.5, 30x2.5 mm².
- 37x1, 37x1.5, 37x2.5 mm².

U-HFFRA m (C) (0,6/1 kV fire resistant armored power cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, copper drain wire, metal coated polyester tape, halogen-free inner covering, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 1x1, 1x1.5, 1x2.5, 1x4, 1x6, 1x10, 1x16, 1x25, 1x35, 1x50, 1x70, 1x95, 1x120, 1x150, 1x185, 1x240, 1x300 mm².
- 2x1, 2x1.5, 2x2.5, 2x4, 2x6, 2x10, 2x16, 2x25, 2x35, 2x50, 2x70, 2x95 mm².
- 3x1, 3x1.5, 3x2.5, 3x4, 3x6, 3x10, 3x16, 3x25, 3x35, 3x50, 3x70, 3x95, 3x120, 3x150, 3x185, 3x240 mm².
- 4x1, 4x1.5, 4x2.5, 4x4, 4x6, 4x10, 4x16, 4x25, 4x35, 4x50, 4x70, 4x95, 4x120, 4x150 mm².
- 5x1, 5x1.5, 5x2.5, 5x4, 5x6, 5x10, 5x16, 5x25, 5x35, 5x50, 5x70, 5x95 mm².
- 7x1, 7x1.5, 7x2.5 mm².
- 8x1, 8x1.5, 8x2.5 mm².
- 10x1, 10x1.5, 10x2.5 mm².
- 12x1, 12x1.5, 12x2.5 mm².
- 16x1, 16x1.5, 16x2.5 mm².
- 18x1, 18x1.5, 18x2.5 mm².
- 19x1, 19x1.5, 19x2.5 mm².
- 24x1, 24x1.5, 24x2.5 mm².
- 27x1, 27x1.5, 27x2.5 mm².
- 30x1, 30x1.5, 30x2.5 mm².
- 37x1, 37x1.5, 37x2.5 mm².

COMMUNICATION CABLES - Models:

- U-HFT m
- U-HFT m (I)
- U-HFT m (C)
- U-HFT m (I+C)
- U-HFAT m
- U-HFAT m (I)
- U-HFAT m (C)
- U-HFAT m (I+C)
- U-HFFRT m
- U-HFFRT m (I)
- U-HFFRT m (C)
- U-HFFRT m (I+C)
- U-HFFRAT m
- U-HFFRAT m (I)
- U-HFFRAT m (C)
- U-HFFRAT m (I+C)

U-HFT m (250 V unarmored communication cables with tinned or bare copper conductors class 2 or 5, XLPE insulation, outer jacket SHF 1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².
- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².
- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².
- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².
- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².

U-HFT m (I) (250 V unarmored communication cables with tinned or bare copper conductors class 2 or 5, XLPE insulation, copper drain wire, metal coated polyester tape, outer jacket SHF 1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².
- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².
- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².
- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².
- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².

U-HFT m (C) (250 V unarmored communication cables with tinned or bare copper conductors class 2 or 5, XLPE insulation, copper drain wire, metal coated polyester tape, outer jacket SHF 1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².
- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².
- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².

U-HFT m (C) (250 V unarmored communication cables with tinned or bare copper conductors class 2 or 5, XLPE insulation, copper drain wire, metal coated polyester tape, outer jacket SHF 1 or SHF 2)

- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².
- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².

U-HFT m (I+C) (250 V unarmored communication cables with tinned or bare copper conductors class 2 or 5, XLPE insulation, copper drain wire, metal coated polyester tape, copper drain wire, metal coated polyester tape, outer jacket SHF 1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².
- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².
- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².
- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².
- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².

U-HFAT m (250 V armored communication cables with tinned or bare copper conductors class 2 or 5, XLPE insulation, halogen-free inner covering, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².
- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².
- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².
- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².
- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².

U-HFAT m (I) (250 V armored communication cables with tinned or bare copper conductors class 2 or 5, XLPE insulation, copper drain wire, metal coated polyester tape, halogen-free inner covering, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².
- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².

U-HFAT m (I) (250 V armored communication cables with tinned or bare copper conductors class 2 or 5, XLPE insulation, copper drain wire, metal coated polyester tape, halogen-free inner covering, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².
- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².
- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².

U-HFAT m (C) (250 V armored communication cables with tinned or bare copper conductors class 2 or 5, XLPE insulation, copper drain wire, metal coated polyester tape, halogen-free inner covering, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².
- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².
- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².
- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².
- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².

U-HFAT m (I+C) (250 V armored communication cables with tinned or bare copper conductors class 2 or 5, XLPE insulation, copper drain wire, metal coated polyester tape, copper drain wire, metal coated polyester tape, halogen-free inner covering, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².
- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².
- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².
- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².
- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².

U-HFFRT m (250 V fire resistant unarmored communication cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, outer jacket SHF1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².
- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².

U-HFFRT m (250 V fire resistant unarmored communication cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, outer jacket SHF1 or SHF 2)

- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².
- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².
- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².

U-HFFRT m (I) (250 V fire resistant unarmored communication cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, copper drain wire, metal coated polyester tape, outer jacket SHF 1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².
- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².
- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².
- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².
- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².

U-HFFRT m (C) (250 V fire resistant unarmored communication cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, copper drain wire, metal coated polyester tape, outer jacket SHF 1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².
- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².
- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².
- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².
- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².

U-HFFRT m (I+C) (250 V fire resistant unarmored communication cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, copper drain wire, metal coated polyester tape, copper drain wire, metal coated polyester tape, outer jacket SHF 1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².
- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².

U-HFFRT m (I+C) (250 V fire resistant unarmored communication cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, copper drain wire, metal coated polyester tape, copper drain wire, metal coated polyester tape, outer jacket SHF 1 or SHF 2)

- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².
- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².
- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².

U-HFFRAT m (250 V fire resistant armored communication cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, halogen-free inner covering, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².
- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².
- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².
- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².
- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².

U-HFFRAT m (I) (250 V fire resistant armored communication cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, copper drain wire, metal coated polyester tape, halogen-free inner covering, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².
- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².
- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².
- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².
- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².

U-HFFRAT m (C) (250 V fire resistant armored communication cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, copper drain wire, metal coated polyester tape, halogen-free inner covering, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².

U-HFFRAT m (C) (250 V fire resistant armored communication cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, copper drain wire, metal coated polyester tape, halogen-free inner covering, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².
- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².
- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².
- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².

U-HFFRAT m (I+C) (250 V fire resistant armored communication cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, copper drain wire, metal coated polyester tape, copper drain wire, metal coated polyester tape, halogen-free inner covering, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 1x2x0.5, 1x2x0.75, 1x2x1, 1x2x1.5, 1x2x2.5 mm².
- 1x3x0.5, 1x3x0.75, 1x3x1, 1x3x1.5, 1x3x2.5 mm².
- 1x4x0.5, 1x4x0.75, 1x4x1, 1x4x1.5, 1x4x2.5 mm².
- 2x2x0.5, 2x2x0.75, 2x2x1, 2x2x1.5, 2x2x2.5 mm².
- 2x3x0.5, 2x3x0.75, 2x3x1, 2x3x1.5, 2x3x2.5 mm².
- 2x4x0.5, 2x4x0.75, 2x4x1, 2x4x1.5, 2x4x2.5 mm².
- 3x2x0.5, 3x2x0.75, 3x2x1, 3x2x1.5, 3x2x2.5 mm².
- 3x3x0.5, 3x3x0.75, 3x3x1, 3x3x1.5, 3x3x2.5 mm².
- 3x4x0.5, 3x4x0.75, 3x4x1, 3x4x1.5, 3x4x2.5 mm².
- 4x2x0.5, 4x2x0.75, 4x2x1, 4x2x1.5, 4x2x2.5 mm².
- 4x3x0.5, 4x3x0.75, 4x3x1, 4x3x1.5, 4x3x2.5 mm².
- 4x4x0.5, 4x4x0.75, 4x4x1, 4x4x1.5, 4x4x2.5 mm².
- 5x2x0.5, 5x2x0.75, 5x2x1, 5x2x1.5, 5x2x2.5 mm².
- 5x3x0.5, 5x3x0.75, 5x3x1, 5x3x1.5, 5x3x2.5 mm².
- 5x4x0.5, 5x4x0.75, 5x4x1, 5x4x1.5, 5x4x2.5 mm².
- 7x2x0.5, 7x2x0.75, 7x2x1, 7x2x1.5, 7x2x2.5 mm².
- 7x3x0.5, 7x3x0.75, 7x3x1, 7x3x1.5, 7x3x2.5 mm².
- 7x4x0.5, 7x4x0.75, 7x4x1, 7x4x1.5, 7x4x2.5 mm².
- 8x2x0.5, 8x2x0.75, 8x2x1, 8x2x1.5, 8x2x2.5 mm².
- 8x3x0.5, 8x3x0.75, 8x3x1, 8x3x1.5, 8x3x2.5 mm².
- 10x2x0.5, 10x2x0.75, 10x2x1, 10x2x1.5, 10x2x2.5 mm².
- 10x3x0.5, 10x3x0.75, 10x3x1, 10x3x1.5, 10x3x2.5 mm².
- 12x2x0.5, 12x2x0.75, 12x2x1, 12x2x1.5, 12x2x2.5 mm².
- 14x2x0.5, 14x2x0.75, 14x2x1, 14x2x1.5, 14x2x2.5 mm².
- 16x2x0.5, 16x2x0.75, 16x2x1, 16x2x1.5, 16x2x2.5 mm².
- 18x2x0.5, 18x2x0.75, 18x2x1, 18x2x1.5, 18x2x2.5 mm².
- 19x2x0.5, 19x2x0.75, 19x2x1, 19x2x1.5, 19x2x2.5 mm².
- 24x2x0.5, 24x2x0.75, 24x2x1, 24x2x1.5, 24x2x2.5 mm².

U-HFFRAT m (I+C) (250 V fire resistant armored communication cables with tinned or bare copper conductors class 2 or 5, fire resistant mica tape, XLPE insulation, copper drain wire, metal coated polyester tape, copper drain wire, metal coated polyester tape, halogen-free inner covering, tinned or bare copper wire braid or galvanized steel wire braid armor, outer jacket SHF 1 or SHF 2)

- 27x2x0.5, 27x2x0.75, 27x2x1, 27x2x1.5, 27x2x2.5 mm².
- 30x2x0.5, 30x2x0.75, 30x2x1, 30x2x1.5, 30x2x2.5 mm².
- 37x2x0.5, 37x2x0.75, 37x2x1, 37x2x1.5, 37x2x2.5 mm².